



PO Box 16017
Hornby
Christchurch 8441

Phone: 03 344 0260

Fax: 03 3498732

info@agrippapaints.co.nz
www.agrippapaints.co.nz



SUPERDECK

Deck & Furniture Stain

PRODUCT INFORMATION

DESCRIPTION:

Durable and protective, innovative, water based, linseed oil, alkyd & acrylic penetrating, semi-transparent colour timber stain.

PROPERTIES:

SUPERDECK Deck & Furniture Stain is a Linseed oil, alkyd and acrylic binder technology has been used to formulate this decking and furniture stain. SUPERDECK Deck & Furniture Stain has the combined properties of penetration of the timber, film hardness to protect walk-on surfaces and outdoor furniture.

SUPERDECK Deck & Furniture Stain contains UV resistant pigments and mould inhibitors and dries to a low sheen finish. Semi-transparent colours retain the natural grain of timber.

PRINCIPAL USES:

Pine timber decks, hardwood timber decks, outdoor furniture, houses, fences. SUPERDECK Deck & Furniture Stain may be used on new and weathered timber as well as previously stained or oiled timber decks after thorough preparation - please refer to "Preparation" before use.

COLOURS:

Semi-transparent Colours: Cactus Red, Desert Oak, Golden Cedar

Note: Always colour test first to check your choice of SUPERDECK Deck & Furniture Stain colour gives the result you want on the actual timber you are staining. Wet colour will darken once dry.

APPLICATION DATA:

Surface Preparation: All surfaces:

Must be sound, clean, dry and free from dirt, oil, grease, mould, moss, soot, lichen, salt, bird droppings and other contaminants. Preparation is the key to the performance of SUPERDECK Deck & Furniture Stain, and timber surfaces need good absorption to enable SUPERDECK Deck & Furniture Stain to penetrate.

We recommend the use of NOVEX TIMBER CLEAN & PREP Fungicidal Treatment & Cleaner for timber deck preparation and NOVEX TREAT-IT Fungicidal Treatment & Cleaner for outdoor furniture preparation.

Note: Heavy water blasting is not recommended as it can "fluff" the timber surface, use a low-medium pressure wash down and/or scrubbing.

Do not use steel wool or wire brushes when preparing the timber surface as iron fragments will result in black spots and staining.

Mould, Moss & Lichen:

If mould, moss or lichen is present, pre-treat the surfaces in advance with NOVEX TIMBER CLEAN & PREP Fungicidal Treatment & Cleaner for timber deck preparation and NOVEX TREAT-IT Fungicidal Treatment & Cleaner for outdoor furniture preparation and leave for at least 2 weeks, then remove dead material and dirt by scraping, scrubbing or pressure washing. Leave to dry.

Note: Removal of these is critical to achieving a successful long-term decorative STAIN system and to achieve this you need to treat, leave until it has died then remove.

New Pine: New decking timber should be weathered for 8 weeks. Clean and treat with the appropriate NOVEX preparatory product before the application of SUPERDECK Deck & Furniture Stain. *Note: Shiny (mill glazed) machined timber surfaces should be sanded to allow penetration.*

Date Issued: October 2025

Page 1 of 3

The information concerning the use and application of our products is supplied in good faith, based on our experience and tests. However, subject to our standard Terms & Conditions of Sale (available on request) and any implied terms, conditions, or warranties imposed by the Consumer Guarantees Act 1993 the recommendations and suggestions herein are made without guarantee, as application conditions are out of our control. Adequate tests should be made to ensure product or recommendations suitability. We reserve the right to alter product or specification without notice.

"There shall be no right of redress against the manufacturer under the Consumer Guarantees Act 1993 in respect of goods which fail to comply with any express guarantees made by the manufacturer in relation to the information contained herein where the goods have failed for reasons beyond the control of the manufacturer".

Application details are based on generic scenarios, for any specific application not mentioned above, details please contact Agrippa Paints directly.

This product would be expected to be fit for purpose and perform as stated in this data sheet, provided the substrate is in good condition and preparation and application is completed as recommended to a high standard and application is carried out by a suitably skilled/experienced applicator.

The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current.

New Hardwood:

Prepare as above.

Due to the nature of hardwoods, we recommend timbers such as Kwila, Hopea, Jarrah & Vitex or any other hardwoods, need to be weathered for 12 weeks before the application of SUPERDECK Deck & Furniture Stain. This assists with the removal of oily tannins and opens the fibres to aid penetration. Rinsing with water several times over this period is beneficial in addition to the use of NOVEX TIMBER CLEAN & PREP to prepare the surface.

Previously Stained & Oiled

Prepare as above.

Clean and treat with the appropriate NOVEX preparatory product. Heavily oiled surfaces may require sanding back to a clean sound surface. If a more natural wood grain look is required, you will need to sand back to bare timber followed by cleaning and treating with the NOVEX TIMBER CLEAN & PREP before the application of SUPERDECK Deck & Furniture Stain.

To remove paint or other coatings back to a bare surface, use a combination of paint stripper/remover and sanding followed by NOVEX TIMBER CLEAN & PREP before applying SUPERDECK Deck & Furniture Stain.

Weathered Pine & Hardwoods:

Prepare as above.

Brush badly weathered timber with a stiff bristle brush to remove any loose and degraded timber. Clean and treat with the appropriate NOVEX preparatory product before the application of SUPERDECK Deck & Furniture Stain. If the natural wood grain is to be restored, badly weathered and greyed timber may require sanding back to a clean sound surface. Clean and treat with NOVEX TIMBER CLEAN & PREP before the application of SUPERDECK Deck & Furniture Stain.

When sanding is required, sand with the timber grain to minimise sanding marks and for larger areas use of a sanding drum or belt is suggested. For coarse sanding use 80-120 grit and smooth use 180-240 grit paper.

Notes: Heavy water blasting is not recommended as it can "fluff" the timber surface, use a low-medium pressure wash down and/or scrubbing.

SUPERDECK Deck & Furniture Stain is not recommended to be used on bamboo or similar products.

Application:

Apply on a fine day. Avoid application if rain is forecast within 24 hours or if the temperature is below 10°C. If applied to hot surfaces, difficult application may be experienced due to rapid evaporation.

Stir well before use with a wide flat stirrer in a circulating "bottom to top" motion.

Apply with a good quality brush or applicator pad.

Apply liberally along the entire length of boards at a time to avoid lapping joints. Work stain well into any crevasses in the timber. Apply only as much stain as the timber will readily absorb. It is good practice to apply a full coat to the board ends and edges where possible.

Two coats are recommended to give greater durability and protection to the timber.

If the project requires more than one pail of product (especially different batches) it is good practice to add some of the new pail to the last of the old pail during application to ensure colour uniformity.

Recoat:

The 1st coat must be touch dry and tack free enough to walk on before recoating. When applying SUPERDECK Deck & Furniture Stain to previously stained surfaces or Hardwood timbers, it is recommended to leave overnight between coats to ensure the 1st coat does not soften when recoated. Absorbent surfaces such as Softwoods (Pine) or well weathered timber may be able to be recoated after a minimum of 2 hours. This varies with timber absorbency, temperature and humidity.

Drying & Curing Time:

As SUPERDECK Deck & Furniture Stain continues to harden and toughen over several days. Allow as long as practical, ensuring a minimum, allow a minimum of 24 hours before light foot traffic. On previously sealed/stained surfaces or Hardwood timbers, dry time will be longer.

Drying and curing times depend upon timber absorbency, temperature and humidity.

Clean-up:

SUPERDECK Deck & Furniture Stain's innovative formulation allows for water clean-up. Wash equipment with cold water then, to remove any oily residue, rinse with hot, soapy water e.g. laundry detergent.

Cleaning rags or paper soaked with linseed oil can spontaneous combust when "bunched up". Hang or spread out rags to dry before disposal according to your local council regulations.

Protect our Environment – When disposing of leftover liquid, keep out of stormwater drains and waterways. Take to a local hazardous waste disposal station. Dry all empty containers in a well ventilated area. Dispose of the empty containers according to your local council regulations.

Maintenance: We recommend washing every 12 months (after each winter is a great time) with NOVEX TREAT-IT Fungicidal Treatment & Cleaner to remove dirt deposits. Dirt, salt and bird deposits left on the surface will encourage the growth of mould and negatively affect the paints performance.

SUPERDECK Deck & Furniture Stain requires reapplication when the timber surface shows signs of heavy weathering. New dressed timber surfaces, including hardwood, may require early maintenance due to limited absorption on initial application.

GENERAL DATA

Gloss Level: Low sheen.

Theoretical Coverage: Allow 6-8 square metres per litre per coat depending on the texture and absorbency of the timber. Rough surfaces use more product.

Application Temperature: 10-25°C

Shelf Life: Store in cool conditions, away from direct sunlight. Under normal conditions full containers can be stored for several years. Check contents before use.

Specific Gravity: Approximately 1 (varies slightly with colour) = 1 kg/litre.

Sizes available: SUPERDECK Deck & Furniture Stain is supplied in 4 and 10 litre plastic containers. Test pots are also available.

COMMON QUESTIONS & ANSWERS

Q Gloss variation's with SUPERDECK Deck & Furniture Stain?

A Gloss variation's can occur due to how much of the stain has been absorbed into the timber fibres. The situation 'evens out' to a low sheen finish over a period of time.

Q Can we mix the colours?

A Yes, colours are fully intermixable. We suggest you experiment with Test Pots to achieve the desired colour and test on an inconspicuous area before proceeding with the entire area.