



PO Box 16017
Hornby
Christchurch 8441

Phone: 03 344 0260

Fax: 03 3498732

info@agrippapaints.co.nz
www.agrippapaints.co.nz



COVERWELL

Water Based Pigmented Sealer

PRODUCT INFORMATION

- DESCRIPTION:** COVERWELL Water Based Pigmented Sealer is a low odour, low VOC, styrene acrylic based Interior sealer ideal for sealing Gib® Board, stopped paper-faced plaster board, and all plastered and cementitious surface around the home.
- PROPERTIES:** COVERWELL Water Based Pigmented Sealer dries to a flat finish with easy sand properties. In application COVERWELL Water Based Pigmented Sealer has minimal roller splatter and is quick drying. COVERWELL Water Based Pigmented Sealer is a fast-drying paint that can be applied on substrates at temperatures as low as 5°C.
- PRINCIPAL USES:** COVERWELL Water Based Pigmented Sealer has been formulated specifically to seal plastered surfaces and paper faced plasterboard throughout the home, providing an even porosity basecoat that ensures an excellent holdout, and an even sheen of any topcoat applied over it. COVERWELL Water Based Pigmented Sealer is also suitable as an undercoat on timber or MDF scotia and skirting boards.
- LIMITATIONS:** On wet area paper faced plaster board such as Gib Aqualine, Sunburnt or Skim Coated plasterboard NOVEX COVERWELL Oil Based Pigmented Sealer should be used.
To seal walls after stripping wallpaper, use NOVEX COVERWELL Oil Based Pigmented Sealer.
Some stopping compounds and plasters can give issues with adhesion of the finished paint system on the feathered edges of stopped areas. If in doubt NOVEX Oil Based Pigmented Sealer should be used.
One coat of COVERWELL Water Based Pigmented Sealer cannot be expected to hold back gross staining. The source of the stain must be removed, and more than one coat of COVERWELL Water Based Pigmented Sealer must be used.
Please refer to "Preparation" before use. On unusual or non-standard surfaces, you should test this product to determine if it is suitable for your particular use.
Do not apply when temperature is below 5°C.
- COLOURS:** White.
- APPLICATION DATA:**
- Surface Preparation:**
- All Surfaces:** All loose, peeling and flaking material must be removed.
Glossy surfaces must be sanded to a dull finish with 200 grit sandpaper, removing sanding dust before applying COVERWELL Water Based Pigmented Sealer.
Fill holes and cracks with a suitable filler. Sand the surface smooth with 150 or 180 grit sandpaper.
Remove grease by washing down with liquid sugar soap as per label directions.
If mould is present remove as much mould growth as possible with a stiff brush. Apply a mixture of 1L hypochlorite bleach and 20mL liquid sugar soap in 3L water by spray or brush, leave for 30 minutes then rinse off and allow the surface to dry. Alternatively, a proprietary fungicidal wash may be used as per label directions.
Allow new plaster to dry for 7 days, sand and dust-off the plaster before application of NOVEX Water-Based Pigmented Sealer.
Ensure all surfaces are clean before application.
- Note:** All sanding dusts can be harmful. When sanding any surface wear an appropriate dust mask. Avoid breathing the dust.

Application: Apply on a fine day. Avoid application if the temperature is below 5°C.
Stir well before use, with a wide flat stirrer in a circulating "bottom to top" motion.
Apply with a good quality brush, 6-8mm nap roller or by airless spray. Brushing is the preferred application method for sealers, as it works the material into the surface ensuring better penetration and adhesion.
Thin up to 10% with water if required to ease application onto very porous surfaces.

Drying Time & Recoat:
As a guide, COVERWELL Water Based Pigmented Sealer will be touch dry in approximately 30 minutes and can be recoated after 2 hours.
When dry lightly sand with 180 or 200 grit sandpaper before overcoating with 2 coats of NOVEX CUBIX Interior Acrylic.

Note: Drying and curing times will vary depending on temperature and humidity conditions at time of application.

Clean-up: Wash equipment with water.

GENERAL DATA

Gloss Level: Flat

Theoretical Coverage:
8-14 square metres per litre per coat depending on porosity and texture of the substrate.

Shelf Life: Store in cool conditions, away from direct sunlight. Under normal conditions, full containers can be stored for several years. Check contents before use.

Specific Gravity: Approximately 1.32 = 1.32 kg/litre.

Sizes Available: COVERWELL Water Based Pigmented Sealer is supplied in 10 Litre pails.

Low VOC: What does "Low VOC" mean? Low VOC paints have a reduced amount of volatile organic compounds. Therefore, the paint won't give off as many fumes, compared to traditional paints. This translates into a more pleasant painting experience.

PROTECT OUR ENVIRONMENT

When disposing of leftover liquid, keep out of stormwater drains and waterways. Take to a local hazardous waste disposal station. Dry all empty containers in a well-ventilated area. Re-use or dispose of the empty containers according to your local council regulations.